# **PlugStation**<sup>®</sup>



# **PLUGSTATION® EARPLUG DISPENSER**

Give workers easy access to hearing protection. With the PlugStation<sup>®</sup>, you can afford to put earplugs in all the places they're needed. PlugStations<sup>®</sup> increase compliance, because their high visibility dispenser increases awareness so you won't waste time looking for earplugs. With the PlugStation<sup>®</sup>, earplugs drop right into the palm of your hand so you don't have to worry about earplugs falling on the floor, or trays collecting dust and contaminants, because the chute is positioned right in front of the turn handle. 100% PVC-Free. Available in 250 or 500 Pairs PlugStations<sup>®</sup>. Includes mounting bracket and hardware. Independently tested to ANSI S3.19-1974.

## **MOLDEX TECHNICAL ASSISTANCE**

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 ext. 512/550 or email: sales@moldex.com or visit www.moldex.com.

# FEATURES

- 100% PVC-Free.
- Gives workers easy access to hearing protection.
- High visibility to increase awareness for your hearing conservation program.
- Eliminates the mess of individually bagged packaging because earplugs drop right into the palm of your hand.
- Each dispenser is sealed and disposable plus completely recyclable.
- Independently tested to ANSI S3.19-1974.
- The bright green color is a trademark of Moldex-Metric, Inc. and also provides easy compliance checks.

MOLDEX @

MOLDEX @ -







#### MEAN ATTENUATION DATA OF SPARKPLUGS GOIN' GREEN® AND CAMO PLUGS®

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	42.3	43.7	46.6	40.9	38.6	44.7	46.9	49.3	48.3	22	A1
Standard Deviation (dB)	5.0	6.0	5.8	4.2	2.8	3.2	3.3	4.2	3.6	33	AL

Independently tested in accordance with ANSI S3.19-1974 by Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 33 decibels.

#### MEAN ATTENUATION DATA OF PURA-CONES"

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	37.2	37.5	37.5	35.3	34.5	42.3	45.5	47.2	47.8	20	Λ1
Standard Deviation (dB)	4.1	4.3	4.6	3.7	2.3	3.0	4.7	3.1	2.9	29	AL

Independently tested in accordance with ANSI S3.19-1974 by

Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 29 decibels.

## **MEAN ATTENUATION DATA OF METEORS®**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	40.7	42.3	41.8	41.2	39.4	45.9	46.3	47.4	47.4	22	A1
Standard Deviation (dB)	5.2	5.1	4.5	3.5	3.2	3.8	4.3	3.8	4.3	33	AL

Independently tested in accordance with ANSI S3.19-1974 by

Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 33 decibels.

## WARNING TO USER

- 1. Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
- 2. Failure to follow all instructions could result in hearing loss or injury. 3. Failure to obtain a proper fit will reduce effectiveness of hearing protectors
- and could result in hearing loss or injury. 4. Meteors, Small are for smaller ear canals only. Moldex offers Meteors
- earplugs in regular size for people with larger ear canals. Failure to use the correct size Meteor for your ear canal size may result in hearing loss. Consult your supervisor or an audiologist before wearing.
- 5. Over protection can be dangerous. The wearer must be able to hear warning signals.
- Wearers with hearing loss should exercise extreme caution.
- 7. It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
- 8. Use caution when working around machinery or any other equipment to ensure neck cord does not become caught or entangled.
- 9. Failure to follow these warnings could result in serious injury or death. 10. Moldex earplugs must only be used as part of a hearing conservation
- program that complies with applicable local safety and health regulations.

#### MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd., Culver City, CA 90232 Tel: +1 (800) 421-0668 or +1 (310) 8376500 Fax: +1 (310) 8379563

Email: sales@moldex.com\_www.moldex.com

## **CANADIAN CUSTOMER SERVICE**

TEL: 310-837-6500, Ext. 517 FAX: 310-837-9563

Moldex Technical Service Department: +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550

Moldex, Ideas that wear well, SparkPlugs, Pura-Fit, Goin' Green, Camo Plugs, Pura-Cones, Traffic Cones, Meteors, PlugStation and the random color patterns are registered trademarks. Pura-Cones and the bright green color are trademarks of Moldex-Metric, Inc. Made in U.S.A.

U.S. Patents #D414,359, #D413,465, #D529,169, #5,954,229, #6,241,120. Made in the U.S.A. 9701-700 REV L 09/09

## **MEAN ATTENUATION DATA OF PURA-FIT®**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	42.4	43.5	45.9	39.8	36.8	445	46.6	48.1	47.4	22	A1
Standard Deviation (dB)	4.9	4.2	4.9	3.4	2.0	3.7	2.9	4.6	4.7	33	AL

Independently tested in accordance with ANSI S3.19-1974 by Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 33 decibels.

#### **MEAN ATTENUATION DATA OF TRAFFIC CONES®**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	48.9	29.1	30.3	31.4	32.1	39.5	41.0	43.3	43.0	22	AL
Standard Deviation (dB)	5.2	4.6	4.7	4.2	3.4	4.0	4.7	5.3	5.0	23	AL

Independently tested in accordance with ANSI S3.19-1974 by

Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 23 decibels.

# **MEAN ATTENUATION DATA OF METEORS® SMALL**

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA
Real Ear Attenuation (dB)	30.2	34.0	35.7	35.6	37.3	41.1	43.1	45.5	43.4	20	A1
Standard Deviation (dB)	5.0	5.0	4.2	3.5	3.1	5.6	5.5	5.3	4.4	28	AL

Independently tested in accordance with ANSI S3.19-1974 by

Michael & Assoc., Inc. State College, PA.EPA Noise Reduction Rating 33 decibels.

## PACKAGING

## PlugStation<sup>®</sup> with SparkPlugs<sup>®</sup>

**6644** - 250 Pairs per Dispenser, 6 Dispensers per Case **6645** - 500 Pairs per Dispenser, 4 Dispensers per Case

#### PlugStation<sup>®</sup> with Pura-Fit<sup>®</sup> 6844 - 250 Pairs per Dispenser, 6 Dispensers per Case 6845 - 500 Pairs per Dispenser, 4 Dispensers per Case

PlugStation<sup>®</sup> with Goin' Green<sup>®</sup>

6646 - 250 Pairs per Dispenser, 6 Dispensers per Case 6647 - 500 Pairs per Dispenser, 4 Dispensers per Case 6674, Individually Boxed 250 Pairs per Dispenser, 6 Dispensers per Case

# PlugStation® with Camo Plugs®

6648 - 500 Pairs per Dispenser, 4 Dispensers per Case

#### LIMITED WARRANTY IMPORTANT NOTICE **TO PURCHASER**

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

#### **DISTRIBUTED BY:**









PlugStation<sup>®</sup> with Pura-Cones<sup>™</sup> 6794 - 250 Pairs per Dispenser, 6 Dispensers per Case 6795 - 500 Pairs per Dispenser, 4 Dispensers per Case

PlugStation<sup>®</sup> with Traffic Cones<sup>®</sup>

PlugStation<sup>®</sup> with Meteors<sup>®</sup>

6744 - 250 Pairs per Dispenser, 6 Dispensers per Case

6745 - 500 Pairs per Dispenser, 4 Dispensers per Case

6875 - 500 Pairs per Dispenser, 4 Dispensers per Case

PlugStation<sup>®</sup> with Meteors<sup>®</sup> Small

6634 - 250 Pairs per Dispenser, 6 Dispensers per Case



