

Special OpsTM Earmuffs



GOOD LOOKS AND STYLE

Camouflage color and sleek, curvy shape for a look that workers will want to wear.

UNIQUE METAL BAND DESIGN

The Camo M1 Premium Earmuff features a black-chrome, spring-steel headband that resists fatigue and is more durable than wire bands. It maintains stability and doesn't twist out of shape like other wire-band earmuffs. Six different adjustment points provide a custom and comfortable fit for most head sizes. M1 folds into a super-compact size for easy storage.

QUICK AND EASY ALIGNMENT

The special molded grips of the Camo M2 Multi-Position Earmuffs make fitting and alignment quick and easy. The cup adjustment is infinitely variable, distributing pressure evenly for a comfortable fit.

MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 ext. 512/550 or E-mail: sales@moldex.com or visit www.moldex.com.

FEATURES

- 100% PVC-Free.
- Camouflage color & sleek curvy shape.
- High NRR ratings.
- M1 Premium Earmuff folds for easy storage.
- M1 has a black-chrome, spring-steel band that doesn't twist out of shape like wire bands.
- M2 has molded grips for easy and quick fitting.
- M1 Premium NRR 29.
- M2 NRR 26 (Over-the-Head).



MOLDEX
Ideas that wear well.

ATTENUATION DATA

M1 (OVER-THE-HEAD)

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	16.4	23.9	27.8	36.2	37.5	43.9	46.1	44.4	42.7	NRR 29	CSA AL
Standard Deviation (dB)	2.8	2.6	2.0	3.5	2.8	3.9	3.6	4.1	4.7		

ATTENUATION DATA

M2 (BEHIND-THE-HEAD)

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	15.3	21.6	25.2	33.1	36.1	41.4	41.3	43.5	40.9	NRR 24	CSA AL
Standard Deviation (dB)	2.4	2.4	2.2	2.4	3.2	3.8	3.4	3.4	4.3		

ATTENUATION DATA

M2 (OVER-THE-HEAD)

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	16.4	23.9	29.4	34.2	35.6	43.7	45.0	43.2	42.1	NRR 26	CSA AL
Standard Deviation (dB)	2.3	2.5	2.3	2.4	2.4	2.4	2.1	2.8	3.1		

ATTENUATION DATA

M2 (UNDER-THE-CHIN)

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	15.5	20.2	25.7	33.5	36.7	42.0	42.2	43.7	40.8	NRR 24	CSA AL
Standard Deviation (dB)	1.9	2.4	2.4	2.1	3.4	2.7	3.0	4.5	4.4		



WARNING TO USER

1. Use this laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending on how the protectors are fitted and worn.
2. Failure to follow all instructions could result in hearing loss or injury.
3. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
4. Earmuffs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
5. Overprotection can be dangerous. The wearer must be able to hear warning signals.
6. Wearers with hearing loss should exercise extreme caution.
7. It is the employer's responsibility to ensure that the type of hearing protector and its NRR is appropriate for the user in their particular workplace.
8. Failure to follow these warnings could result in serious injury or death.

PACKAGING

6109 Special Ops™, M1 Camo Earmuff

1 Earmuff per Box
10 Boxes per Case

6209 Special Ops™, M2 Camo Earmuff

1 Earmuff per Box
20 Boxes per Case

6105 Earmuff Hygiene Kit

1 Kit per Bag
20 Bags per Case

LIMITED WARRANTY IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. **Exclusive Remedies:** damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

DISTRIBUTED BY:

MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd., Culver City, CA 90232
Tel: +1 (800) 421-0668 or +1 (310) 837-6500 Fax: +1 (310) 837-9563
Email: sales@moldex.com www.moldex.com

Moldex Technical Service Department: +1 (800) 421-0668 or +1 (310) 837-6500 Ext. 512/550

CANADIAN CUSTOMER SERVICE

TEL: +1 (310) 837-6500, Ext. 517
FAX: +1 (310) 837-9563

Moldex and Ideas that wear well are registered trademarks.
Special Ops is a trademark of Moldex-Metric, Inc.
U.S. Patents #D459,034, #D459,033, #D464,469, #D463,857 and #6,353,938
Made in U.S.A.
9702-746 REV D 07/09



Printed on Recycled Paper



MOLDEX
Ideas that wear well.