

# **Soft Comfortable Fit**

Mellows earplugs are made of extra-soft, extra-light foam. Their tapered shape fits easily in the ear canal, and seals gently and snugly without pressure. They're so comfortable you'll forget you're wearing earplugs.

# **All-Day Wear**

The low pressure, smaller design of Mellows is perfect for extended periods of wear. Mellows provide maximum foam comfort with the appropriate protection for mid to high level noise areas.

# **High Visibility Colors**

A very bright orange plug color and neon green cord color provide for easy and quick compliance checks.

# MELLOWS™ FOAM EARPLUGS

- Extra-soft, extra-light foam for superior all-day comfort
- High visibility colors make compliance checks quick and easy
- Tapered shape for easy insertion and removal
- Shaped to fit even very small ear canals
- Non-irritating smooth surface
- 100% PVC Free
- Independently tested to ANSI S3.19-1974, NRR 30dB
- Independently tested to AS/NZS 1270, SLC<sub>80</sub> 22dB, Class 4























#### ATTENUATION DATA / DATOS DE ATENUACIÓN / DONNÉES D'ATTÉNUATION

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA. Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA. Tests Conformes aux Spécs. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB) Atenuación de Dato (dB) Atténuation Moyenne (dB)	26.2	32.3	41.0	37.8	38.3	47.3	47.7	48.0	45.7	NRR	CSA
Standard Deviation (dB) Desviación Standard (dB) Écart Standard (dB)	3.4	4.0	4.4	3.7	2.5	4.6	3.4	3.5	4.3	30	AL

# ATTENUATION DATA FOR AUSTRALIA / NEW ZEALAND

Tested According to AS/NZS 1270 by Michael & Assoc.

Note: For full details of methods of selecting a hearing protector, see AS/NZS 1269.3

Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269.3, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

Frequency (Hz)	125	250	500	1000	2000	4000	8000	
Mean Attenuation (dB)	19.0	20.1	24.6	24.6	31.1	36.0	39.7	
Standard Deviation (dB	6.8	7.2	8.5	6.2	5.2	8.3	8.6	SLC <sub>80</sub> 22dB,
Mean Minus Standard Deviation (dB)	12.1	12.9	16.2	18.4	26.0	27.8	31.1	Class 4

# MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd., Culver City, CA 90232 Tel: +1 (800) 421-0668 or +1 (310) 837-6500

Fax: +1 (310) 837-9563

 ${\it Email: sales@moldex.com\ www.moldex.com}$ 

### **CANADIAN CUSTOMER SERVICE**

Tel: +1 (800) 421-0668, Ext. 517 Fax: +1 (310) 837-9563

# **AUSTRALIA**

UNIT 30/14-16 STANTON ROAD, SEVEN HILLS, NSW 2147 Tel: +61 02 9838 7588 Fax: +61 02 9838 7544 Email: moldex@bigpond.net.au www.moldex.com

# **NEW ZEALAND**

3 Spence Road, Henderson, Auckland, NZ Tel: +64 (9) 837 8247 Fax: +64 (9) 837 8248 Email: trevorc@moldex.com www.moldex.com

Moldex, Ideas that wear well and the PVC-Free logo are registered trademarks. Mellows is a trademark of Moldex-Metric, Inc. U.S. Patents Pending.

6820-807 REV A 09/10

#### **WARNINGS TO USER**

- Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
- 2. Failure to follow all instructions could result in hearing loss or injury.
- Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
- 4. Over protection can be dangerous. The wearer must be able to hear warning signals.
- 5. Wearers with hearing loss should exercise extreme caution.
- 6. It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
- 7. Failure to follow these warnings could result in serious injury or death.
- 8. Mellows earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
- Use caution when working around machinery or other equipment to ensure neck cord does not become caught or entangled.

# **PACKAGING**

Description	Quantity	Case
6820 Mellows Uncorded	200 Pairs per Box	10 Boxes per Case
6840 Mellows Corded	100 Pairs per Box	20 Boxes per Case
6846 Mellows PlugStation	250 Pairs per PlugStation	6 per Case
6847 Mellows PlugStation	500 Pairs per PlugStation	4 per Case

# LIMITED WARRANTY - IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. Exclusive Remedies: damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damage, or liability, direct, indirect, incidental, special, or consequential, arising out of sale, use, or misuse, or the inability to use products by the user.

# **DISTRIBUTED BY:**

























